

## Cirago BTA-3190 USB Bluetooth® Adapter - Mini

### Benefits and Features

- CSR Single Chip BC4 EDR
- *Bluetooth* Specification 2.0 EDR class 2
- Enhanced Data Rate (EDR) compliant for both 2Mbps and 3Mbps modulation modes
- Full speed *Bluetooth* operation with full Piconet and Scatternet support
- Support for 802.11 co-existence
- RoHS compliant
- Full speed USB v 2.0 interface support OHCI and UHCI host interface
- Receiver Sensitivity -90dBm
- Stable, accurate search ability
- Supports: Windows Vista, XP, 2000, ME, 98; Mac OS 8.6+, Linux



Description	
Standard	<i>Bluetooth</i> 2.0 specification, Class 2
Operating System Support	Vista, XP, 2000, Mac OS 10.1.4 or above, Linux
Operating Range	10 Meters (33 feet)
Operating Frequency	2.402 GHz - 2.4835 GHz ISM Band
Connection	Point-to-Point
RF Output power	+4dBm , 0dBm ( Class 2)
Power Supply	USB Powered
Transmit Power	1 mW
Dimension	0.625" x 2.5" x 0.25"

Box Qty	Box Dimensions
40pcs	17" x 23.5" x 9.25"